

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

BASF Aktiengesellschaft**AE 20030434/Kes****PF 0000055529/Kes****- 14 -****Claims**

1. A process for preparing polyether polyols having an end block of ethylene oxide by addition of alkylene oxides onto H-functional starter substances, in which
- 5
- A) a polyether polyol precursor is prepared by means of double metal cyanide (DMC) catalysis in a semicontinuous mode of operation in which previously prepared polyether polyol together with the DMC catalyst are placed in a reactor and H-functional starter substance and propylene oxide are added continuously,
- 10
- B) the polyether polyol precursor from stage A) is reacted with propylene oxide or an ethylene oxide/propylene oxide mixture in the presence of the DMC catalyst in a continuously operating reactor to give a polyether polyol intermediate,
- 15
- C) the intermediate from stage B) is mixed with an alkali metal hydroxide as catalyst and
- 20
- D) reacted with ethylene oxide in a continuously operating reactor to give the final product,
- E) the catalyst is separated off from the final product obtained in stage D).
- 25
2. A process according to claim 1, wherein the polyether polyol precursor prepared in stage A) has from 10 to 80% of the molar mass of the final product.
- 30
3. A process according to claim 1 or 2, wherein the polyether polyol precursor prepared in stage A) has an OH number of from 50 to 400 mg KOH/g.
- 35
4. A process according to any of claims 1 to 3, wherein the polyether polyol intermediate prepared in stage B) has from 50 to 95% of the molar mass of the final product.

B03/0434US IB/XS/jw

April 21, 2004

BASF Aktiengesellschaft**AE 20030434/Kes PF 0000055529/Kes****- 15 -**

5. A process according to any of claims 1 to 4, wherein stage B) is carried out in a continuously operated stirred tank reactor (CSTR).
- 5 6. A process according to any of claims 1 to 4, wherein stage B) is carried out in a continuously operated jet loop reactor having internal heat exchanger tubes.
- 10 7. A process according to any of claims 1 to 4, wherein stage B) is carried out in a continuously operated, completely filled circulation reactor.
8. A process according to any of claims 1 to 7, wherein the catalyst suitable for ethoxylation is selected from among KOH, amines and Lewis acids.
- 15 9. A process according to claim 8, wherein the catalyst is separated off from the final product in stage E) by adding water to the reaction mixture obtained in stage D and effecting phase separation in a coalescer.